

2-unit to 5-unit Multi-split Indoor Units Specifications

Wall-mounted type

Model name	Indoor unit		ASYG07KGTE	ASYG09KGTE	ASYG12KGTE	ASYG14KGTE
kW Class			2.0	2.5	3.5	4.0
Power Source			Single phase, ~230 V, 50 Hz			
Sound Pressure Level	Cooling	H/M/L/Q	38/33/29/21	40/34/29/21	40/35/30/21	43/36/30/21
			Heating	41/35/31/22	42/36/31/22	42/38/33/22
Sound Power Level	Cooling	H	54	55	56	57
			Heating	56	57	58
Airflow Rate	Cooling	H/M/L/Q	650/540/430/270	700/560/430/270	700/560/430/270	770/600/450/280
			Heating	720/580/460/330	750/610/470/330	770/640/520/330
Net Dimensions			mm 270 × 834 × 215			
Weight			kg (lbs) 10 (22)			
Connection Pipe Diameter	Liquid/Gas	mm	6.35/9.52			



Wall-mounted type

Model name	Indoor unit		ASYG07KETE ASYG07KETE-B	ASYG09KETE ASYG09KETE-B	ASYG12KETE ASYG12KETE-B	ASYG14KETE ASYG14KETE-B
kW Class			2.0	2.5	3.5	4.0
Power Source			Single phase, ~230 V, 50 Hz			
Sound Pressure Level	Cooling	H/M/L/Q	38/33/29/21	40/34/29/21	40/35/30/21	43/36/30/21
			Heating	41/35/31/22	42/36/31/22	42/38/33/22
Sound Power Level	Cooling	H	54	55	55	57
			Heating	56	57	58
Airflow Rate	Cooling	H/M/L/Q	650/540/430/270	700/560/430/270	700/560/430/270	770/600/450/280
			Heating	720/580/460/330	750/610/470/330	770/640/520/330
Net Dimensions			mm 295 × 950 (wall side: 840) × 230			
Weight			kg (lbs) 11 (24)			
Connection Pipe Diameter	Liquid/Gas	mm	6.35/9.52			



Wall-mounted type

Model name	Indoor unit		ASYG07KMCE	ASYG09KMCE	ASYG12KMCE	ASYG14KMCE
kW Class			2.0	2.5	3.5	4.0
Power Source			Single phase, ~230 V, 50 Hz			
Sound Pressure Level	Cooling	H/M/L/Q	38/33/29/21	40/34/29/21	40/35/30/21	43/36/30/21
			Heating	41/35/31/22	42/36/31/22	42/38/33/22
Sound Power Level	Cooling	H	54	55	55	57
			Heating	56	57	58
Airflow Rate	Cooling	H/M/L/Q	650/540/430/320	700/560/430/320	700/560/430/320	770/600/450/310
			Heating	720/580/460/330	750/610/470/330	780/640/520/330
Net Dimensions			mm 270 × 834 × 222			
Weight			kg (lbs) 10 (22)			
Connection Pipe Diameter	Liquid/Gas	mm	6.35/9.52			



Wall-mounted type

Model name	Indoor unit		ASYG18KMTE	ASYG22KMTE	ASYG24KMTE
kW Class			5.0	6.0	7.0
Power Source			Single phase, ~230 V, 50 Hz		
Sound Pressure Level	Cooling	H/M/L/Q	45/40/35/29	48/40/35/29	49/40/35/29
			Heating	46/40/35/29	48/40/35/29
Sound Power Level	Cooling	H	60	62	65
			Heating	61	62
Airflow Rate	Cooling	H/M/L/Q	980/810/640/510	1,060/810/640/510	1,170/850/640/510
			Heating	1,020/850/640/510	1,060/850/640/510
Net Dimensions			mm 280 × 980 × 240		
Weight			kg (lbs) 12.5 (27)		
Connection Pipe Diameter	Liquid/Gas	mm	6.35/12.70		



Floor

Model name	Indoor unit		AGYG09KVCA	AGYG12KVCA	AGYG14KVCA
kW Class			2.5	3.5	4.0
Power Source			Single phase, ~230 V, 50 Hz		
Sound Pressure Level	Cooling	H/M/L/Q	39/34/28/22	42/36/30/22	44/38/31/22
			Heating	39/35/30/22	42/38/32/22
Sound Power Level	Cooling	H	52	55	56
			Heating	52	55
Airflow Rate	Cooling	H/M/L/Q	530/440/360/270	600/490/380/270	650/520/400/270
			Heating	530/460/380/270	600/510/410/270
Net Dimensions			mm 600 × 740 × 200		
Weight			kg (lbs) 14 (31)		
Connection Pipe Diameter	Liquid/Gas	mm	6.35/9.52		



Ceiling

Model name	Indoor unit		ABYG18KRTA	ABYG22KRTA
kW Class			5.0	6.0
Power Source			Single phase, ~230 V, 50 Hz	
Sound Pressure Level	Cooling	H/M/L/Q	38/36/33/31	42/37/34/31
			Heating	38/36/33/31
Sound Power Level	Cooling	H	53	57
			Heating	53
Airflow Rate	Cooling	H/M/L/Q	840/790/710/650	900/790/710/650
			Heating	840/790/710/650
Net Dimensions			mm 235 × 1,080 × 705	
Weight			kg (lbs) 24 (52)	
Connection Pipe Diameter	Liquid/Gas	mm	6.35/12.70	




Compact Cassette Grid Type

Model name	Indoor unit		AUXG07KVLA	AUXG09KVLA	AUXG12KVLA	AUXG14KVLA	AUXG18KVLA	AUXG22KVLA
kW Class			2.0	2.5	3.5	4.0	5.0	6.0
Power Source			Single phase, ~230 V, 50 Hz					
Sound Pressure Level	Cooling	H/M/L/Q	33/31/29/27	33/31/29/27	37/34/31/28	38/35/32/29	38/35/32/29	44/42/36/30
			Heating	34/32/29/27	34/32/29/27	37/34/31/29	43/38/34/30	43/38/34/30
Sound Power Level	Cooling	H	46	46	49	50	50	56
			Heating	47	47	49	55	55
Airflow Rate	Cooling	H/M/L/Q	540/490/440/390	540/490/440/390	610/530/470/410	680/580/490/410	680/580/490/410	830/740/600/450
			Heating	540/490/440/390	540/490/440/390	610/530/470/410	790/680/580/450	790/680/580/450
Net Dimensions			mm 245 × 570 × 570					
Weight			kg (lbs) 15 (33)					
Panel			UTG-UFYF-W					
Connection Pipe Diameter	Liquid/Gas	mm	6.35/9.52					




Mini duct

Model name	Indoor unit		ARXG07KSLAP	ARXG09KSLAP	ARXG12KSLAP	ARXG14KSLAP	ARXG18KSLAP
kW Class			2.0	2.5	3.5	4.0	5.0
Power Source			Single phase, ~230 V, 50 Hz				
Sound Pressure Level	Cooling	H/M/L/Q	29/26/24/23	29/26/24/23	31/27/25/23	35/30/27/23	33/29/26/23
			Heating	29/26/24/23	29/26/24/23	31/27/25/23	35/30/27/23
Sound Power Level	Cooling	H	52	54	55	60	58
			Heating	53	56	57	62
Airflow Rate	Cooling	H/M/L/Q	550/440/390/360	600/450/400/360	650/490/430/360	800/640/530/360	940/750/540/480
			Heating	550/440/390/360	600/450/400/360	650/490/430/360	800/640/530/360
Net Dimensions			mm 198 × 700 × 450				
Weight			kg (lbs) 15.5 (34)				
Connection Pipe Diameter	Liquid/Gas	mm	6.35/9.52				
External static pressure			Pa 0 to 30				
Drain pump			Standard				



Slim duct

Model name	Indoor unit		ARXG07KLLAP	ARXG09KLLAP	ARXG12KLLAP	ARXG14KLLAP	ARXG18KLLAP
kW Class			2.0	2.5	3.5	4.0	5.0
Power Source			Single phase, ~230 V, 50 Hz				
Sound Pressure Level	Cooling	H/M/L/Q	28/26/25/24	28/27/26/25	29/28/27/26	32/30/28/26	32/30/29/27
			Heating	28/26/25/24	28/26/25/24	29/28/27/24	32/30/28/25
Sound Power Level	Cooling	H	57	57	58	60	58
			Heating	57	57	58	60
Airflow Rate	Cooling	H/M/L/Q	550/490/470/440	600/550/500/450	650/600/550/480	800/700/600/480	940/880/820/750
			Heating	550/490/470/440	600/550/500/450	650/600/550/480	800/700/600/480
Net Dimensions			mm 198 × 700 × 620				
Weight			kg (lbs) 17 (37)				
Connection Pipe Diameter	Liquid/Gas	mm	6.35/9.52				
External static pressure			Pa 0 to 90				
Drain pump			Standard				



Medium Static Pressure Duct

Model name	Indoor unit		ARXG22KMLB
kW Class			6.0
Power Source			Single phase, ~230 V, 50 Hz
Sound Pressure Level	Cooling	H/M/L/Q	31/29/27/25
			Heating
Sound Power Level	Cooling	H	60
			Heating
Airflow Rate	Cooling	H/M/L/Q	1,100/910/750/580
			Heating
Net Dimensions			mm 270 × 1,135 × 700
Weight			kg (lbs) 35 (77)
Connection Pipe Diameter	Liquid/Gas	mm	6.35/12.70
External static pressure			Pa 30 to 150
Drain pump			Standard

